ENG: The measurements mentioned in the drawings and in TimberIN websites are only approximate data. They will differ from the measurements of the finished product. It is due to the fact that our products are individually designed and hand-made. However, if one or more measurements are very important, please mention before ordering. We will pay big attention to your requirements in the production process. This will ensure that the product will be produced as closely as possible to your requirements.

DE: Die in den Zeichnungen und auf den TimberIN-Websites genannten Maße sind nur ungefähre Angaben. Sie unterscheiden sich von den Maßen des fertigen Produkts. Dies liegt daran, dass unsere Produkte individuell gestaltet und handgefertigt werden. Wenn jedoch eine oder mehrere Messungen sehr wichtig sind, geben Sie dies bitte vor der Bestellung an. Wir werden Ihre Anforderungen im Produktionsprozess sehr berücksichtigen. Dadurch wird sichergestellt, dass das Produkt so genau wie möglich Ihren Anforderungen entspricht.

FR: Les mesures mentionnées dans les dessins et sur les sites Web TimberIN ne sont que des données approximatives. Ils différeront des mesures du produit fini. Cela est dû au fait que nos produits sont conçus individuellement et fabriqués à la main. Cependant, si une ou plusieurs mesures sont très importantes, merci de le mentionner avant de commander. Nous prêterons une grande attention à vos besoins dans le processus de production. Cela garantira que le produit sera fabriqué aussi près que possible de vos besoins.

DK: Målingerne nævnt på tegningerne og på TimberIN-websteder er kun omtrentlige data. De afviger fra målingerne af det færdige produkt. Det skyldes, at vores produkter er individuelt designet og håndlavet. Hvis en eller flere målinger dog er meget vigtige, skal du nævne det før du bestiller. Vi vil være meget opmærksomme på dine krav i produktionsprocessen. Dette vil sikre, at produktet produceres så tæt som muligt efter dine krav.

NO: Målingene nevnt på tegningene og på TimberIN nettsteder er bare omtrentlige data. De vil avvike fra målingene av det ferdige produktet. Det skyldes det faktum at produktene våre er individuelt designet og håndlaget. Imidlertid, hvis en eller flere målinger er veldig viktige, må du nevne før du bestiller. Vi vil ta stor vekt på dine krav i produksjonsprosessen. Dette vil sikre at produktet blir produsert så nært som mulig dine behov.

IT: Le misure menzionate nei disegni e nei siti Web di TimberIN sono solo dati approssimativi. Differiranno dalle misure del prodotto finito. È dovuto al fatto che i nostri prodotti sono progettati e realizzati a mano individualmente. Tuttavia, se una o più misurazioni sono molto importanti, si prega di menzionare prima di ordinare. Presteremo grande attenzione alle vostre esigenze nel processo di produzione. Ciò garantirà che il prodotto sarà prodotto il più vicino possibile alle vostre esigenze.

NL: De in de tekeningen en op TimberIN-websites genoemde metingen zijn slechts benaderende gegevens. Ze zullen verschillen van de afmetingen van het eindproduct. Het is te wijten aan het feit dat onze producten individueel zijn ontworpen en met de hand zijn gemaakt. Als een of meer metingen erg belangrijk zijn, vermeld dit dan voordat u bestelt. We zullen veel aandacht besteden aan uw eisen in het productieproces. Dit zorgt ervoor dat het product zo dicht mogelijk bij uw eisen wordt geproduceerd.

SWE: Mätningarna som nämns på ritningarna och på TimberIN-webbplatser är endast ungefärliga data. De kommer att skilja sig från måtten på den färdiga produkten. Det beror på att våra produkter är individuellt designade och handgjorda. Om en eller flera mätningar är mycket viktiga, berätta dock innan du beställer. Vi kommer att ägna stor uppmärksamhet åt dina krav i produktionsprocessen. Detta kommer att säkerställa att produkten produceras så nära dina krav som möjligt.

PL: Pomiary wymienione na rysunkach i na stronach internetowych TimberIN są jedynie danymi przybliżonymi. Będą się różnić od pomiarów gotowego produktu. Wynika to z faktu, że nasze produkty są indywidualnie zaprojektowane i wykonane ręcznie. Jeśli jednak co najmniej jeden pomiar jest bardzo ważny, należy o tym wspomnieć przed złożeniem zamówienia. Zwrócimy dużą uwagę na Twoje wymagania w procesie produkcyjnym. Zapewni to, że produkt będzie produkowany jak najbliżej Twoich wymagań.


RECTANGULAR WOODEN OUTDOOR SAUNA TECHNICAL SHEET

TimberIN
BALTIC SPA & SAUNAS

Table of contents


GENERAL MEASUREMENTS 3
2000 MM RECTANGULAR SAUNA 4
3000 MM RECTANGULAR SAUNA 7
4000 MM RECTANGULAR SAUNA 12
5000 MM RECTANGULAR SAUNA 18
WOOD BURNING HARVIA HEATERS 24
WOOD BURNING HARVIA HEATER SAFETY DISTANCES APPLIED IN TIMBERIN SAUNAS 25
ELECTRIC HARVIA HEATERS 26
THERMAL INSULATION 27
PANORAMIC WINDOW TYPES 28
STANDARD WINDOW 28
PANORAMIC WINDOW (GLASS AREA 50%) 29
PANORAMIC WINDOW (GLASS AREA 100%) 30

GENERAL MEASUREMENTS



3D view of this model

2000 MM RECTANGULAR SAUNA




MODEL	2000 MM
Seating capacity	2 - 4
Length	2040 mm
Height (without chimney)	2450 mm
Width	2340 mm
Weight	~800 kg
Wood type	Spruce Larch Thermowood
Recommended official “Harvia” heater	Harvia M3 Harvia M3 SL Harvia Cilindro 9 kW


3D view of this model

INTERIOR LAYOUT

MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	2040 mm
Length inside	1900 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm




DELIVERY INFO



MODEL 2000 MM	DELIVERY INFO
Assembled sauna measurements	Height: 2620 mm Width: 2400 mm Length: 2080 mm Weight ~800 kg

3000 MM RECTANGULAR SAUNA




MODEL	3000 MM
Seating capacity	4 - 6
Length	3040 mm
Height (without chimney)	2450 mm
Width	2340 mm
Weight	~1100 kg
Wood type	Spruce Larch Thermowood
Recommended official “Harvia” heater	Harvia M3 Harvia M3 SL Harvia Cilindro 9 kW

3D view of this model

INTERIOR LAYOUT (1)

3 m sauna


MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	3040 mm
Length inside	2900 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm




INTERIOR LAYOUT (2)


1m dressing room + 2m sauna

MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	3040 mm
Length inside	950 mm and 1810 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm



BASE MEASUREMENTS






Please note that the base of the sauna may differ depending on the type of construction.


If that makes any influence on your order, please contact us separately and we will give all required information

DELIVERY INFO



MODEL 3000 MM	DELIVERY INFO
Assembled sauna measurements	Height: 2620 mm Width: 2400 mm Length: 3080 mm Weight ~1100 kg

4000 MM RECTANGULAR SAUNA




MODEL	4000 MM
Seating capacity	6 - 8
Length	4040 mm
Height (without chimney)	2450 mm
Width	2340 mm
Weight	~1400 kg
Wood type	Spruce Larch Thermowood
Recommended official “Harvia” heater	Harvia 20 PRO Harvia 20 SL Cilindro 11 kW

3D view of this model

INTERIOR LAYOUT (1)

4 m sauna


MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	4040 mm
Length inside	3900 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm



INTERIOR LAYOUT (2)

1 m dressing room + 3 m sauna


MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	4040 mm
Length inside	950 mm and 2810 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm




INTERIOR LAYOUT (3)


1,5 m dressing room + 2,5 m sauna

MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	4040 mm
Length inside	1450 mm and 2310 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm



BASE MEASUREMENTS






Please note that the base of the sauna may differ depending on the type of construction.

If that makes any influence on your order, please contact us separately and we will give all required information

DELIVERY INFO




MODEL 4000 MM	DELIVERY INFO
Assembled sauna measurements	Height: 2620 mm Width: 2400 mm Length: 4080 mm Weight ~1400 kg

Mobein

5000 MM RECTANGULAR SAUNA

TimberIN
BALTIC SPA & SAUNAS




MODEL	5000 MM
Seating capacity	8 - 10
Length	5040 mm
Height (without chimney)	2450 mm
Width	2340 mm
Weight	~1700 kg
Wood type	Spruce Larch Thermowood
Recommended official “Harvia” heater	Harvia 20 PRO Harvia 20 SL Cilindro 13 kW

3D view of this model

INTERIOR LAYOUT (1)

5 m sauna


MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	5040 mm
Length inside	4900 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm



INTERIOR LAYOUT (2)

1 m dressing room + 4 m sauna


MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	5040 mm
Length inside	950 mm and 3810 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm




INTERIOR LAYOUT (3)


1,5 m dressing room + 3,5 m sauna

MODEL	INTERIOR LAYOUT of not insulated sauna
Length outside	5040 mm
Length inside	1450 mm and 3310 mm
Width outside	2340 mm
Width inside	2260 mm
Door width	620 mm
Width of the benches	580 mm



BASE MEASUREMENTS






Please note that the base of the sauna may differ depending on the type of construction.

If that makes any influence on your order, please contact us separately and we will give all required information

DELIVERY INFO



MODEL 5000 MM	DELIVERY INFO
Assembled sauna measurements	Height: 2620 mm Width: 2400 mm Length: 5080 mm Weight ~1700 kg

WOOD BURNING HARVIA HEATERS

Recommended for 2 – 4 meter sauna room
Harvia M3 + chimney



The Harvia M3 has a classic design and is suitable for smaller, woodburning saunas. It turns a sauna bath into a pleasurable experience and adds a touch of traditional sauna atmosphere. The even heat and efficient air circulation guarantee an enjoyable bath.

Output 16,5 kW

Stones max. 30 kg

User manual HERE

Recommended for 2 - 4 meter sauna room
Harvia M3 SL + chimney (logs loaded from outside instead of inside)



The SL models are designed for people who want to conveniently heat their sauna from another room or outside the building. SL stoves provide great bathing in small and medium-sized saunas.

Output 16,5 kW

Stones max. 30 kg

User manual HERE

Recommended for 4 – 5 meter sauna room
Harvia 20 PRO + chimney



Harvia 20 Pro gives a good hot bath in medium-sized saunas. It has a big stone space and an air-flow spoiler made of stainless steel. Through the cast-iron glass door the warm glow of the fire adds to the sauna atmosphere.

Output 24,1 kW

Stones max. 40 kg

User manual HERE

Recommended for 4 – 5 meter sauna room
Harvia 20 SL + chimney (logs loaded from outside instead of inside)



The SL models are designed for people who want to conveniently heat their sauna from another room or outside the building. SL stoves provide great bathing in small and medium-sized saunas.

Output 24,1 kW

Stones max. 40 kg

User manual HERE

WOOD BURNING HARVIA HEATER SAFETY DISTANCES APPLIED IN TIMBERIN SAUNAS ACCORING TO OFFICIAL HARVIA HEATERS SAFETY REQUIREMENTS

HARVIA M3 / HARVIA M3 SL:

- Walls and benches made of inflammable materials. The minimum safety distances to inflammable materials:
  - on either side – 25 cm (B),
  - behind the stove – 30 cm (C), *due to installed cetris panel behind the heater the distance can be minimized,*
  - in the front – approx. 30 cm (D).
- Heater ground area is covered with cetris panel.

Harvia 20 PRO / Harvia 20 SL:

- Walls and benches made of inflammable materials. The minimum safety distances to inflammable materials:
  - on either side – 30 cm (B),
  - behind the stove – 30 cm (C), *due to installed cetris panel behind the heater the distance can be minimized,*
  - in the front – approx. 30 cm (D).
- Heater ground area is covered with cetris panel.

SAUNA CHIMNEY:

- Non insulated chimney min. 50 cm from inflammable materials (*side materials can be cover with cetris panel to reduce the distance*).
- Insulation between roof and insulated chimney min. 10 cm.
- Chimney insulation going down from the roof min. 43 cm.

	A min.	B min.	C min.	D min.
M1, M2, M3/SL, Classic 140	1200	250	300	300
20 Pro, 20 SL/Duo, 20 ES Pro/S, 20 Boiler, 20 SL Boiler, Premium/VS, Classic 220/Duo, 20 RS/LS Pro	1300	300	300	300
26 Pro, Classic 280	1280	375	375	375
36, 36 Duo	1250	500	500	500
Linear 16, 16	1300	300	350	400
Linear 22, 22/S, Linear 22 RS/LS/ES, 22 RS/LS/ES S	1265	400	380	500
Linear 28	1380	400	400	500




Figure 1 Safety distances (all dimensions in millimeters)





Figure 2 Safety distances for chimney (all dimensions in millimeters)

ELECTRIC HARVIA HEATERS

Recommended for 2 – 3 meter sauna room Cilindro 9 kW (PC90) with an integrated control unit	Recommended for 4 meter sauna room Cilindro 11kW (PC110XE) including a digital Harvia Xenio control panel.
 Harvia Cilindro electric heater's massive sauna stone amount provides enjoyable sauna bath. Cilindro has an apertured outer casing made of stainless steel. You can adjust the nature of the heat from soft to sharp by throwing water either to the side of the heater or straight on top of the stone pillar. **Output 9 kW** **Stones max. 80 kg** **User manual HERE**	 Harvia Cilindro 110EX heaters provide a smooth, yet powerful heat in saunas of all sizes. Exterior made from stainless steel looks impressive and is a great addition to any sauna. Sauna temperature can be seen in the digital display. **Output 10.8 kW** **Stones max. 120 kg** **User manual HERE**

inMberin

THERMAL INSULATION



THE CROSS-SECTION VIEW OF INSULATED OUTDOOR SAUNA`S WALL

The first one (1) represents the wooden panels (44 mm thick).

The second one (2) – humidity barrier. The main aim of the humidity barrier is to eliminate the penetration of water or vapor to the insulation layer (3).


The nature of humidity barrier from outside and inside is different. The outside layer waterproofs the insulation and the inside humidity barrier does not allow the vapor to penetrate to the insulation layer. They both are very thin therefore their thickness is not mentioned.

The fourth (4) and the last layer is interior wooden panels, they are 20 mm of thickness. They are needed to support the insulation layer. It must be noted that the humidity barrier from the outside does not necessarily always have to be there. It depends on the type of sauna. The external wooden panels which form the wall of sauna are usually covered with bituminous shingles which act as waterproofing layer as well.

If you need more information then check our article HERE

PANORAMIC WINDOW TYPES


STANDARD WINDOW



STANDARD WINDOW
Height: 450 mm Width: 640 mm

**Please note that the manufacturer depending on the model might install wooden edges for decorative / constructional purposes.


PANORAMIC WINDOW (GLASS AREA 50%)



PANORAMIC WINDOW (GLASS AREA 50%)
Height: 1110 mm Width: 2260 mm

**Please note that the manufacturer depending on the model might install wooden edges for decorative / constructional purposes.

PANORAMIC WINDOW (GLASS AREA 100%)



PANORAMIC WINDOW (GLASS AREA 100%)
Height: 2130 mm Width: 2260 mm

**Please note that the manufacturer depending on the model might install wooden edges for decorative / constructional purposes.

INFORMAZIONI AGGIUNTIVE

Le pagine seguenti aggiungono informazioni TimberIN aggiornate (dati al 11/2026) alla scheda tecnica originale delle pagine precedenti. Se un dettaglio è diverso, chiedeteci; vale il disegno d’ordine approvato.

In questa sezione

STUFE HARVIA 32
ISOLAMENTO TERMICO (OPZIONALE) 33
COLORI DEL TETTO E ACCESSORI 34
VERSIONE MOBILE – NORDIC SQUARE MOBILE SAUNA 35
RIMORCHIO (VERSIONE MOBILE) 36


STUFE HARVIA

Stufa	Tipo	Potenza	Sauna	
Harvia M3 + camino	Legna, caricata dall’interno	16,5 kW	2–4 m	Inclusa
Harvia M3 SL + camino	Legna, caricata dall’esterno	16,5 kW	2–4 m	Opzione
Harvia 20 PRO + camino	Legna, caricata dall’interno	24,1 kW	4–5 m	Opzione
Harvia 20 SL + camino	Legna, caricata dall’esterno	24,1 kW	4–5 m	Opzione
Harvia Cilindro PC90	Elettrica, centralina integrata	9 kW	2–3 m	Inclusa
Harvia Cilindro PC90XW WiFi Steel	Elettrica, comando Wi-Fi	9 kW	2–3 m	Opzione
Harvia Legend PO110FC WiFi	Elettrica, comando Wi-Fi	10,8 kW	secondo il volume	Opzione

Una stufa è inclusa nel prezzo: la M3 con camino o la Cilindro PC90; sceglietene una sola. Sauna = solo l’ambiente riscaldato, senza spogliatoio né terrazza. Il riscaldamento dipende dal volume, dalle vetrate e dall’isolamento; confermiamo la stufa per il vostro progetto finale.

Alimentazione elettrica: PC90 / PC90XW 400 V 3N~, 3 × 16 A, cavo 5 × 2,5 mm²; PC90 anche 230 V 1N~, 1 × 40 A; Legend PO110FC 400 V 3N~. Un elettricista qualificato dimensiona alimentazione, cavo e protezioni secondo il manuale della stufa.

ISOLAMENTO TERMICO (OPZIONALE)



1. Doghe esterne in legno, 44 mm

2. Barriera all’umidità (esterna): mantiene asciutto l’isolante


3. Isolante

4. Barriera al vapore (interna): impedisce al vapore di raggiungere l’isolante

5. Rivestimento interno in legno, 20 mm

La barriera all’umidità esterna non serve su tutti i modelli. L’isolamento è un’opzione, montata in fabbrica e consigliata per le saune montate; c’è un’opzione per le saune da 2–3 m e una per quelle da 4–5 m. Materiale e spessore esatti sono confermati nell’ordine.

COLORI DEL TETTO E ACCESSORI



Nero **Marrone** **Verde**


Tegole bituminose sul tetto; un colore per sauna.

Accessori (opzionali)
Serbatoio d’acqua in acciaio inox per stufe a legna (effetto vapore)
Impianto elettrico: luci LED sotto le panche
2 lampade Harvia sopra la porta d’ingresso
Protezione in legno davanti alla stufa

VERSIONE MOBILE – NORDIC SQUARE MOBILE SAUNA

La TimberIN Nordic Square Mobile Sauna™ è la versione mobile della TimberIN Nordic Square Barrel™: la stessa sauna, costruita per viaggiare sul proprio rimorchio stradale.

Lunghezze	2, 3, 4 e 5 m (lunghezza totale nominale), abete o Thermowood
Come la Nordic Square Barrel™	Stufe Harvia, isolamento, finestre e configurazioni: vedere le pagine precedenti
Ingresso laterale	Opzione su tutte le lunghezze
Misure	Le misure esterne sono leggermente ridotte perché la sauna stia sul rimorchio e nel camion di consegna; valgono le misure del vostro disegno d'ordine
Rimorchio	Rimorchio frenato a due assi opzionale (categoria UE O2), adattato alla lunghezza della sauna; la sauna da 2 m usa il rimorchio da 3 m. Dati alla pagina seguente
Consegna	Solo montata in fabbrica. Con il rimorchio, la sauna arriva montata su di esso; le ruote del rimorchio vengono smontate per il trasporto e in cantiere serve una gru o un carrello elevatore



Disegno schematico, non in scala. Misure in mm, indicative; vale il disegno d'ordine approvato.

RIMORCHIO (VERSIONE MOBILE)

Ogni sauna mobile TimberIN può essere ordinata sul proprio rimorchio stradale, costruito per il trasporto di una sauna. La lunghezza del rimorchio è adattata alla lunghezza della sauna scelta.

Tipo	Rimorchio a pianale ad asse centrale, a due assi, con pavimento e freni, per il trasporto di una sauna
Categoria UE del veicolo	O2
Assi	2 assi frenati
Pneumatici	4 × 185R14C 104N M+S
Cerchi	5,5J × 14 H2, ET30, 5 × 112
Posizione delle ruote	All’esterno del pianale
Giunto	Giunto a repulsione; altezza di aggancio 430 mm dal suolo (fissa)
Impianto luci	12 V, spina a 13 poli
Ruotino d’appoggio	60 mm
Piedini di stazionamento angolari	4
Cunei per ruote	2
Larghezza del pianale	1,5 m o 2,0 m; 2,07 m a richiesta
Lunghezza del pianale	Adattata alla lunghezza della sauna scelta
Esempio: pianale 5,0 × 2,0 m	Lunghezza totale 6.501 mm incluso il timone; larghezza del pianale 2.000 mm
Esempio: lunghezza di carico 4,0 m	Lunghezza totale 5.520 mm; larghezza totale 1.960 mm; altezza 760 mm (a vuoto)
Omologazione e documenti	Omologato UE (direttiva 2007/46/CE). Fornito con certificato di conformità (COC) e certificato dei dati di identificazione per l’immatricolazione; può essere immatricolato in modo permanente negli Stati membri dell’UE.

Consegna e scarico. Se ordinata con il rimorchio, la sauna viene consegnata già montata su di esso. A causa del limite di altezza del camion, le ruote del rimorchio vengono smontate per il trasporto. Sul posto deve essere disponibile un mezzo di sollevamento, gru o carrello elevatore, per scaricare la sauna dal camion, rimontare le ruote e appoggiare il rimorchio a terra.